









<https://jspsafety.info/EVOGuard-C>

EVOGuard™ C INDUSTRIAL BROWGUARD SYSTEM

- ✓ Optical class 1, K&N and up to A-rated impact visor
- ✓ Innovative all-in-one moulded carrier and visor design
- ✓ Visors fully compatible with EVO® helmet range



EVOGuard™ C INDUSTRIAL VISOR SPECIFICATION

EN 166	EN 166										EN 170		Visor /Frame Material	Weight (g)	
	A - High Energy Impact (190m/s)	B - Medium Energy Impact (120m/s)	T - High Speed Particles at Extreme Temperatures	1 - Optical Class	3 - Liquid droplets Et splash	9 - Molten Metals	K - Anti Scratch	N - Anti Mist	8 - Short Circuit Electric Arc	1 - Electric Arc	0 - Visible Light Transmittance	2C - 1, 2 - UV Filter with Enhance Colour Recognition			Increased Chemical Resistance
	ADA240-060-000		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	Polycarbonate Clear Visor	185
	ADA250-060-000	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	Polycarbonate Clear Visor	185
	ADA260-070-000	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	Co-Polyester Clear Visor	209
	ADA270-070-000	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	Polycarbonate Clear Visor	216
	ADA280-070-000	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	Polycarbonate Clear Visor	216

If the symbols F, B and A are not common to both the ocular and frame then it is the lower level which shall be assigned to the complete eye-protector.



Fully compatible with EVOGuard™ Brownguard



Compatible with:



COMPLETE SYSTEM



EVOGuard™ C2 Industrial Brownguard System
ADB28A-100-400

VIDEO &
INFORMATION



<https://jpsafety.info/EVOGuard-MFB>






















EVOGuard™ M FORESTRY BROWGUARD SYSTEM

- ✓ Up to 80% Visible Light Transmittance
- ✓ Innovative all-in-one moulded carrier and visor design
- ✓ Visors fully compatible with EVO® helmet range



EVOGuard™ M FORESTRY VISOR SPECIFICATION

			EN 1731	S - Increased Robustness	F - Low Energy Impact (45m/s)	Frame Material	Visible Light Transmittance	Visor Material	Weight (g)
	ADA290-080-000						65%		65
	ADA300-080-000						68%		75
	ADA310-080-000						80%		86



Fully compatible with
EVOGuard™ Browguard




Compatible with:



COMPLETE SYSTEM



EVOGuard™ M Forestry Helmet System
AKE24A-500-800



<https://jpsafety.info/EVOGuard-MFH>

EVOGuard™ M FORESTRY HELMET SYSTEM

- ✓ Exceptional head, hearing, eye and face protection
- ✓ Wide field of vision with 80% Visible Light Transmittance
- ✓ Comfortable and secure fit

